

TEGERA® 9128

Synthetic leather glove, winter-lined, 0,7 mm Microthan®+, diamond grip pattern, polyester, fleece, Thinsulate™ 40g, Cat. II, black, yellow, chrome free, high visibility colour, for touchscreen, waterproof, elasticated 360°, for allround work

PROPERTIES

Flexible, durable, excellent grip, perfect fit, extra comfortable

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

COLLECTION PRO

PALM MATERIAL Microthan®+

PALM THICKNESS 0,7 mm

BACK MATERIAL Polyester

LINING Winter-lined

LINING MATERIAL Fleece, Thinsulate™ 40g

CLO LINING 0,7 m²-K/W

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

FASTENING Elasticated 360°

LENGTH RANGE 240-275 mm

COLOUR Black, Yellow

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 0

DISPLAY Hook with hangtag OUTER MATERIAL SPECIFICATION Polyurethane, nylon, polyester

MIDDLE MATERIAL SPECIFICATION Polyethylene

INNER MATERIAL SPECIFICATION Polyester



MicroThan®+

AQUATHAN®



Thinsulate
INSULATION

SIZE	ART. NO.	EAN NO.
6	9128-6	7340118354798
7	9128-7	7392626070868
8	9128-8	7392626070882
9	9128-9	7392626070905
10	9128-10	7392626070820
11	9128-11	7392626070844
12	9128-12	7340118354781

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 9128

FEATURES

For touchscreen, chrome free, high visibility colour, reinforced index finger, reinforced seams, reinforced fingertips, pre-curved fingers, specially designed thumb, knuckle protection, windproof, waterproof, ergonomically shaped, reflector, specially designed details

PREVENTS RISK OF

Chrome allergy, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with moisture, contact with damp, contact with cold

PRIMARY ENVIRONMENTS OF USE

Dark environments, windy environments, slippery environments, dry environments, cold environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Agricultural work, airport work, building and construction, carpentry, construction, engineering, forest work, gardening, machine driving, machine operating, repair work, soil preparation, transport work, warehouse work, wood industry work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction, logistics, HoReCa, facilities, service, retail

TYPE OF WORK

Medium weight

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
1121X



EN 511:2006
111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-10

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 9128

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	1	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003 + A1:2009



EN 388:2016 1121X



EN 511:2006 111



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-10

3(3)