



| SIZE | ART. NO. | EAN NO. |
|------|----------|---------------|
| 9 | 132A-9 | 7340118312163 |
| 10 | 132A-10 | 7340118312040 |
| 11 | 132A-11 | 7340118312064 |
| 12 | 132A-12 | 7340118312088 |
| 13 | 132A-13 | 7340118312101 |
| 7 | 132A-7 | 7340118312125 |
| 8 | 132A-8 | 7340118312149 |

TEGERA® 132A

Welding and heat-resistant glove, fully lined, 0,8-1,2 mm full grain goatskin of top quality, full grain cowhide of top quality, cut resistance level C, KEVLAR® fiber, Cat. III, black, brown, reinforced seams, water and oil repellent, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, durable, good grip, perfect fit

SPECIFICATION

TYPE OF GLOVE Welding gloves

CATEGORY Cat. III

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 15,03

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12, 13

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,8-1,2 mm

BACK MATERIAL Full grain cowhide of top quality

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 3

CUFF STYLE Safety cuff

CUFF MATERIAL Leather

FASTENING Elasticated 180°

LENGTH RANGE 310-370 mm

COLOUR Black, Brown

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 0

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, natural latex

MIDDLE MATERIAL SPECIFICATION Para-aramid

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



TEGERA® 132A

FEATURES

Cut resistant according to 388:2016 level C, withstands contact heat up to 100°C, reinforced seams, water and oil repellent

PREVENTS RISK OF

Burn injuries, heat injuries, cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp, contact with oil

PRIMARY ENVIRONMENTS OF USE

Warm environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Engineering, hot work, metalwork, mining, sheet-metal work, welding

PRIMARY INDUSTRIES OF USE


Mining, oil, gas, petrochemical, metal fabrication, machinery and equipment, MRO, automotive

TYPE OF WORK

Medium weight

CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3X22C  EN 407:2004 41324X EN 12477:2001 + A1:2005

Type A EN 1149-2:1997 R:0.130x10⁹Ω 

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-01-08

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 132A

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

| Property | Level Achieved | (Maximum Performance) |
|--|----------------|-----------------------|
| a) Resistance to abrasion (No. of revolutions) | 3 | (4) |
| b) Cut resistance (Index) | X | (5) |
| c) Tear resistance (N) | 2 | (4) |
| d) Puncturing resistance (N) | 2 | (4) |
| e) Cut resistance, EN ISO 13997 (N) | C | (F) |
| f) Impact protection, EN 13594:2015 | | (P) |

EN 388 – Testing

(specifies the requirements that apply for each safety level).

| Level of protection/Performance level | 1 | 2 | 3 | 4 | 5 |
|--|-----|-----|-------|-------|------|
| a) Resistance to abrasion (No. of revolutions) | 100 | 500 | 2 000 | 8 000 | |
| b) Cut resistance (Index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 |
| c) Tear resistance (N) | 10 | 25 | 50 | 75 | |
| d) Puncturing resistance (N) | 20 | 60 | 100 | 150 | |

| Level of protection/Performance level | A | B | C | D | E | F |
|---------------------------------------|---|---|----|----|----|----|
| e) Cut resistance, EN ISO 13997 (N) | 2 | 5 | 10 | 15 | 22 | 30 |

| Level of protection/Performance level | P |
|---------------------------------------|-----------------------|
| f) Impact protection, EN 13594:2015 | Pass (Level 1 ≤ 9 kN) |

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN 12477:2001 + A1:2005 Protective gloves for welders


Type A - Lower dexterity (with higher other performance)

EN 1149-2:1997 Electrostatic properties (vertical resistance)



CE 2777 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 3X22C  EN 407:2004 41324X  EN 12477:2001 + A1:2005

Type A EN 1149-2:1997  R:0.130x10⁹Ω

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.